

WELDY

Set for universal plastics processing



HT 330-S



HT 330-S Universal Kit

- + Cooling stages
- + Heat protection to prevent burns
- + Ergonomically shaped handle
- + Suspension device (spring-loaded suspension)
- + Easy to use

The HT 330-S Universal Kit is suitable for various professional and industrial indoor hot air applications. In addition to the heat gun, the set includes a wide-slot nozzle, a tube nozzle and a spoon reflector.




Technical data

Voltage [V]	100	120	230
Power [W]	1200	1400	2000
Frequency [Hz]	50/60		
Temperature [°C]	80–600		
Length [mm]	359		
Device diameter [mm]	90		
Weight [g]	650		
Conformity marking	CE		
Protection class II	□		

Article numbers

HT 330-S, 100V/1200W, JP plug	128.727
HT 330-S, 120V/1400W, US plug	128.770
HT 330-S, 230V/2000W, AU plug	128.779
HT 330-S, 230V/2000W, CN plug	128.780
HT 330-S, 230V/2000W, EU plug	128.781
HT 330-S, 230V/2000W, UK plug	128.782

Included accessories

	Glass protection nozzle (Ø 35.5) 50×5 mm	119.341
	Tubular nozzle (Ø 35.5) Ø 20 mm, 30 mm	119.343
	Spoon reflector (Ø 35.5) 40×35 mm	119.344



HT 530-A



HT 530-A Universal kit

- + Configurable, multifunctional button (Miracle Key)
- + Sensor-controlled Eco mode saves energy
- + Quick temperature selection via multifunction knob
- + Adjustable temperature limiter
- + Five accessories included in the set

The HT 530-A universal kit from Weldy is suitable for various indoor plastic welding jobs and hot air applications. In addition to the HT 530-A heat gun, five useful accessories are included in the kit.






Technical data

Voltage [V]	100	120	230
Power [W]	1300	1500	2300
Frequency [Hz]	50/60		
Temperature [°C]	80–650		
Length [mm]	359		
Device diameter [mm]	90		
Weight [g]	700		
Conformity marking	CE		
Protection class II	□		

Article numbers

HT 530-A, 100V/1300W, JP plug	129.473
HT 530-A, 120V/1500W, US plug	129.475
HT 530-A, 230V/2300W, AU plug	129.550
HT 530-A, 230V/2300W, CN plug	129.551
HT 530-A, 230V/2300W, EU plug	129.552
HT 530-A, 230V/2300W, UK plug	129.553

Included accessories

	Spoon reflector (Ø 35.5) 40×35mm	119.344
	Tubular nozzle (Ø 35.5) Ø 6mm, 75mm	119.345
	Wide slot nozzle (Ø 35.5) 25×3mm	119.346
	Soldering reflector (Ø 35.5) 13×5×10mm	119.347
	Pressure roller 30mm, ABS	119.348





Available accessories	HT 330-S	HT 530-A	Available accessories	HT 330-S	HT 530-A
 119.342 Wide slot nozzle (Ø 35.5) 50x3 mm	●	●	 147.248 Tacking nozzle (Ø 8.0)		●
 119.346 Wide slot nozzle (Ø 35.5) 25x3 mm		●	 130.146 Pressure roller 30 mm, silicone	●	●
 146.740 Speed welding nozzle (Ø 8.0) Profile D Ø 4		●	 130.611 Pressure roller 40 mm, silicone	●	●
 127.833 Speed welding nozzle (Ø 8.0) Profile B 70-7		●	 165.036 Heat protection	●	●
 119.343 Tubular nozzle (Ø 35.5) Ø 20 mm, 30 mm	●	●	 119.177 Contour scraper	●	●
 119.345 Tubular nozzle (Ø 35.5) Ø 6 mm, 75 mm		●	 119.178 Contour scraper set	●	●
 129.410 Tubular nozzle (Ø 35.5) Ø 8 mm, 42 mm, 15°		●	 132.050 Welding seam carriage		●
 119.341 Glass protection nozzle (Ø 35.5) 50x5 mm	●	●	 153.894 Quarter moon knife		●
 119.344 Spoon reflector (Ø 35.5) 40x35 mm	●	●	 154.089 Spring balancer	●	●
 119.347 Soldering reflector (Ø 35.5) 13x5x10 mm		●	 115.355 Welding rod, PP, profile D Ø 4, beige		●
 133.174 Smoothing nozzle (Ø 8.0)		●	 115.366 Welding rod, HDPE, profile D Ø 4, black		●



Leister Technologies AG

Galileo-Strasse 10
6056 Kaegiswil
Switzerland

+41 41 662 74 74
leister@leister.com

www.leister.com

USA

Leister Technologies LLC
+1 855 534 7837
info.usa@leister.com

Italy

Leister Technologies
Italia s.r.l.
+39 02 2137647
sales@leister.it

China

Leister Technologies Ltd.
+86 21 6442 2398
leister@leister.cn

Benelux

Leister Technologies
Benelux BV
+31 (0)30 2199888
info@leister.nl

Japan

Leister Technologies KK
+81 6 6310 62 00
sales-japan@leister.com

Germany

Leister Technologies
Deutschland GmbH
+49-(0)2331-95940
info.de@leister.com

India

Leister Technologies
India Pvt
+91 44 2454 3436
info@leister.in