

Air pressure test manometer with new improved tapered testing needle

The reliable and handy air pressure test manometer from Leister is the perfect solution for testing the integrity of dual track seams. The new and improved tapered testing needle makes it easier to obtain an airtight seal between needle and geomembrane. The new tapered needle is also more stable and resistant to breakage.



- Easy and precise seam testing
- High security due to hand and needle protection
- Practical storage case
- New needle interchangeable with current test needle

Article no.:

New tapered testing needle

-	-
150.720	Air pressure test manometer with
	new tapered testing needle
150.142	Spare needle

Standard testing needle

142.475 Air pressure test manometer with testing needle 142.569 Spare needle

Included in delivery are storage case and o-rings



Easy and precise non-destructive seam testing on the construction site



Included in delivery: storage case with spare O-rings

Leister Technologies Italia srl Leister Technologies India Pvt 600 041 Chennai India

> phone: +91 44 2454 3436 info@leister.in

Test manometer / 07.2011 / 02.2015 / ENG

Switzerland phone: +41 41 662 74 74 eister@leister.com

Leister Technologies AG

Galileo-Strasse 10

6056 Kaegiswil

Article no.: 150.142

Leister Technologies LLC Itasca, IL 60143

Not included in delivery: Spare needle

phone: +1 855 534 7837 info@leisterusa.com

PRC

Leister Technologies Ltd. Leister Technologis KK Shanghai 201 109 Yokohama 222-0033 Japan

phone: +86 21 6442 2398 leister@leister.cn phone: +81 45 477 36 37 info@leister.co.jp

Leister Technologies Benelux BV 3991 CE Houten Nederland

phone: +31 (0)30 2199888 info@leister.nl

20090 Segrate Italia

phone: +39 02 2137647 info@leister.it

© Copyright by Leister, Switzerland